

Dektite Shingle Flashings

Perfect for flashing pipes and cables on shingle roofs

Dektite SHR

For Shingle Roof Retrofit Applications on Electrical Masts, Re-Roofing etc.

- ✓ Pipe OD range 0-150mm (clearly marked cutting grooves).
- ✓ Available in black, made from proprietary polymer material compatible with asphalt shingles.
- ✓ Slide down the pipe without cutting, or cut along the zipper and use the clips supplied for retrofitting.
- ✓ Aluminum flange nails securely to the roof.
- ✓ Twenty year warranty. Just fit it and forget it - we've got you covered.

CODE	TO FIT PIPE SIZE	BASE SIZE	ROOF PITCH
DSR103B	0 - 150mm	380 x 380mm	10 - 45°



Dektite SHT

- ✓ Thermoplastic hard base with elastomer collar. Compatible with asphalt shingles. No caulk, self-sealing.
- ✓ 85°C continuous heat.

CODE	TO FIT PIPE SIZE	BASE SIZE	ROOF PITCH
DST101B	32 - 40mm	330 x 235mm	Up to 45°
DST102B	50mm	330 x 235mm	Up to 45°
DST103B	75mm	380 x 285mm	Up to 45°
DST104B	100mm	405 x 305mm	Up to 45°

