

Silicone Sealants



The following silicones have been trialled and have been found to provide a satisfactory bond between the EPDM and Silicone Dektites and most commonly used roofing materials.

- **OCI Professional Roof and Gutter N-192, Silicone Sealant**
- Sikasil AP Multipurpose Silicone Sealant.
- Selleys Roof & Gutter Silicone Sealant.
- Bostik Findley Roof & Gutter Silicone Sealant.
- Dow Corning 791 Silicone Weatherproofing Sealant.

CODE	DESCRIPTION	BOX	COLOUR
N-192	All purpose neutral silicone	20	TRANSPARENT

- For adequate bonding all surfaces must be clean and dry.
- The base of the Dektite should be moulded by hand to form a snug fit to the roof profile.
- The Dektite should then be lifted clear and a continuous bead of neutral cure 100% silicone sealant (roof and gutter approved) applied to the whole of the ribbed underside of the Dektite. For an effective seal a 1-3mm bead of silicone is sandwiched between the two surfaces.
- Pull the Dektite down to sit snugly on the roof profile and fasten with washered screws / Hex screws. NB: Screw coatings of class 4 or 5 are required.
- Remove excess silicon and collect any swarf.

Dektite Pipe Flashing Warranties

This warranty on Dektite Pipe Flashing is given by Consolidated Alloys (NZ) Ltd 55 Maurice Road, Penrose Auckland, New Zealand for the periods and under the terms and conditions listed below.

1. DLM warrants that all Dektite pipe flashings will perform in accordance with our published specifications and will be free from defects in material and workmanship for a maximum period of 20 years, commencing from the date of delivery to end user.

Under this warranty DLM will, at its option, repair or replace any defective Products. Any claim should be made in writing within 60 days following the discovery of any defect. DLM shall not be liable for any costs incurred in the removal of defective items or installation of replacement items nor cost of freight and other associated charges.

2. This warranty shall not apply where:-

- (a) the Product has not been installed in strict accordance with our published recommendations;
- (b) the Product has been installed in an area which has been exposed at any time during the warranty period to corrosive

conditions including but not limited to, corrosive chemicals, ash, fumes or condensates or harmful substance generated within or about the building(s) or fixture(s) to which the Product has been applied;

(c) any damage to the Product has been caused as a result of the negligence or misuse of the Product by the claimant.

(d) any modification to the specification of the Product has been made, save and except where any modification is reasonably necessary in adopting the Product to size.

(f) defects are a result of acts of God or other external forces, including but not limited to, failure to provide free drainage of water from around the areas in which the Product has been installed.

3. To the extent permitted by law, this warranty is given in lieu of all other warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose. Where so permitted, the remedies stated herein are exclusive remedies and DLM shall not be responsible for any indirect, consequential or incidental damages or further loss of any kind whatsoever except as expressly provided by in this Warranty.