

Dektite Premium


The versatile solution

- ✓ Most extensive range of Dektites for flashing penetrations 0 - 510mm, available in black and grey EPDM and silicone red for high temperatures.
- ✓ Designed to enable practically any pipe flashing operation to be carried out within minutes, simple to install and very effective.
- ✓ The low profile cone not only looks good but provides a generous internal clearance, so even the steepest roofs are handled with ease.
- ✓ Suitable for flashing pipes that penetrate wall claddings.
- ✓ Can also be used to flash square penetrations. Just add 30% to the pipe diameter and trim the cone to suit.

- ✓ EPDM withstands temperatures from -50°C to 115°C and up to 150°C intermittently.
- ✓ Silicone withstands temperatures from -60°C to 200°C and up to 250°C intermittently.




Installation Instructions:




NOTE:


For more effective drainage, always fit the Dektite on the diamond or bias.
Dektites are suitable for flashing pipes that penetrate wall claddings.




Cut a neat hole in roofing sheet with minimum clearance for pipe and insert pipe through hole. Trim the cone to suit pipe size using sharp tin snips. Where required, support cut sections of sheet with additional framing.




Slide Dektite flashing down over pipe. Lubricating the pipe with water allows the pipe to slide snugly into position.



Apply a neutral cure 100% silicone sealant (roof and gutter approved) to the underside of the Dektite by turning back the flexible flange.



Press base to the roof profile by hand, smooth out any awkward creases. Don't fully extend to allow for vibration.



Fasten using self drilling washers and sealed rivets. Fit fasteners progressively outward in opposing pairs to avoid gaps.