

# Sheet Lead and Acrylead

Time proven reliability



- ✓ Conforms to AS/NZ1804 – 1976
- ✓ 50 year warranty (on base metal)
- ✓ Extremely malleable
- ✓ Proven quality and performance

## DLM Sheet Lead

- Sheet Lead is the softest of all the common metals, it is extremely malleable; it is capable of being shaped to most profiles at ambient temperatures.
- Sheet lead is a tried and proven product used in the construction industry for hundreds of years, mainly used as weatherings and flashings.
- The most important feature of any well designed roof is the flashing detail. The use of Sheet Lead will ensure that quality and performance are not compromised.
- DLM Sheet Lead is ideal for applications of radiation shielding, sound proofing, chimney flashings, lead slate for pipe penetrations, apron and abutment flashing, canopies and projections, curved parapets, windows and door flashings.

## Range of thickness and weight

Weight (Kg/m <sup>2</sup> )	Nominal Thickness (mm)	Typical Uses
6	0.50	Strip edge for metal flashing, sound proofing.
12	1.0	Sound and radiation proofing.
17	1.50	Apron and cover flashings, hip and ridge flashings, pitched valley gutters, lead slates, chimney flashings and weatherings to cornices, parapets etc. Full roof cladding.
20	1.80	
25	2.25	
30	2.65	Parapet, box and tapered gutters or situations that demand extra length.
35	3.15	
40	3.55	

## DLM Acrylead

- Acrylead has a factory applied thermo baked acrylic primer coating on both sides of the sheet. The process developed by DLM inhibits the contact of water runoff with the lead and its oxides, reducing the potential of the run off staining adjacent materials, and entering ground water systems.
- Acrylead allows you to improve the look of exposed flashings by finish coating of your choice to match roof or surrounding trim colours.

## Recommended maximum sizes of individual pieces of lead for all applications

Weight (Kg/m <sup>2</sup> )	Maximum Length (mm)	Maximum overall girth (mm)
17	1300	600
20	1500	750
25	2000	800
30	2250	850
35	2500	900
40	3000	1000

## E2 / AS1 Compliance

- DLM Sheet Lead and Acrylead are the only apron/abutment flashings that can meet and exceed the 50 YEAR WARRANTY offered by Concrete, Clay, and Slate Tile manufacturers and is a must for compliance with E2/AS1.

## Standard Roll Sizes

**Sheet lead: Both 3m and 6m rolls:** 150, 300, 375mm  
**3m rolls only:** 450, 600, 750, 900mm

**Acrylead: 6m rolls:** 150, 300, 340, 375mm  
**3m rolls only:** 450, 600mm