



Handy Pack Sizes:

50mm x 3m
75mm x 3m

Roll Sizes:

50mm x 10m
75mm x 10m
100mm x 10m
150mm x 10m
200mm x 10m

WEATHERPROOFING REPAIR TAPE



Adheres permanently to clean dry surfaces including:

- ✓ Metals
- ✓ Brick
- ✓ Cement
- ✓ Glass
- ✓ Fibreglass
- ✓ PVC
- ✓ Timber

Stop Leak Flashing Tape is a polyester fused aluminium foil coated with thick Butyl rubber adhesive used for weathersealing joints and seams. Uses include repairs to roofing, guttering, downpipe or water tank tops, sealing joints around skylights, doors or adjoining building surfaces and weathersealing seams in caravans, trucks, toolsheds etc. Stop Leaks is not a permanent solution in replacing existing weather flashings on the home.

Instructions for use:

1. Thoroughly clean and dry surfaces prior to applying Stop Leak Flashing Tape.
2. If surface is porous or crumbling, prime with a Butyl primer.
3. Stop Leak Flashing Tape may be cut with a knife or scissors.
4. Apply Stop Leak Flashing Tape firmly to substrate, smooth down and mould in place.
5. Overlap adjoining strips by a minimum of 25mm.
6. Application temperature 5°C - 40°C. May be warmed to aid adhesion if cold.



Tel: 09 622 9100
Email: enquiries@dmlwallace.co.nz
Web: www.dlm.co.nz

