

BULLNOSING AND PARAPET FLASHING

The wall to roof gap to be flashed should not exceed 145mm. Fasten Dekstrip®, preferably to down side of rib, 170mm away from the wall. Fasten the non-stretched side onto the roof commencing at the rear, finishing at the gutter. Unlike other applications, the Dekstrip® needs stretching in a **CERTAIN AREA ONLY** called the **BEND AREA** (see diagram), therefore fasten the wall edge up to the **"BEND AREA"**, then stretch the edge, form to shape and continue fastening to completion.

Recommendations:


a) Fastening-

Minimum head size of 10mm.

b) Joining-


Metal strips are provided with 10 metre rolls for joining purposes.

(Not supplied with Bullnose pack as they are not required.)



INTERNAL CORNERS VALLEY OR CONCAVE

FIXING TO TOP SHEETS FOR THE ELIMINATION OF LEAF AND TWIG BUILD UP




1 Cut strip to required length.

2 Commence fastening progressively and opposite in the valley of the corrugations using a liberal amount of sealant* under all edges. The Strip Flashing need only be stretched in area of rib misalignment.

EXPANSION JOINTS

Dekstrip allows for thermal expansion and contraction of box gutters.

- Fix evenly across the box gutter; keeping it flat and avoiding creases at corners.
- Ensure fixing points are well sealed with good quality washers and fasteners or sealed, washered rivets.



*Refer to page 28 for silicone usage

Dektite® Pipe Flashing Warranty

This warranty on Dektite® Pipe Flashing is given by DEKS Industries Pty Ltd 493 Mountain Highway, Bayswater, 3153, Victoria, Australia ("DEKS"), for the periods and under the terms and conditions listed below.

1. DEKS warrants that all Dektite® Pipe Flashings including Dekfit® Fittings ('the Products') furnished, will perform in accordance with our published specifications and will be free from defects in material and workmanship for a maximum period of 20 years, commencing from the date of delivery to end user.

Under this warranty DEKS will, at its option, repair or replace any defective Products. Any claim should be made in writing within 60 days following the discovery of any defect. DEKS shall not be liable for any costs incurred in the removal of defective items or installation of replacement items nor cost of freight and other associated charges.

2. This warranty shall not apply where:-

- (a) the Product has not been installed in strict accordance with our published recommendations;
- (b) the Product has been installed in an area which has been exposed at any time during the warranty period to corrosive conditions including but not limited to, corrosive chemicals, ash, fumes or condensates or harmful substance generated within or about the building(s) or fixture(s) to which the Product has been applied;
- (c) any damage to the Product has been caused as a result of the negligence or misuse of the Product by the claimant.
- (d) any modification to the specification of the Product has been made, save and except where any modification is reasonably necessary in adopting the Product to size.
- (e) defects in the Product are a result of mechanical or chemical damage, which occurred during shipment or storage prior to use;
- (f) defects are a result of acts of God or other external forces, including but not limited to, failure to provide free drainage of water from around the areas in which the Product has been installed.

3. To the extent permitted by law, this warranty is given in lieu of all other warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose. Where so permitted, the remedies stated herein are exclusive remedies and DEKS shall not be responsible for any indirect, consequential or incidental damages or further loss of any kind whatsoever except as expressly provided by in this Warranty.

Deks Industries Pty Ltd

ABN 77 109 135 544

